STATE OF CALIFORNIA - STATE LANDS COMMISSION GEOPHYSICAL SURVEY PERMIT - PRE-SURVEY NOTIFICATION FORM SLC 602

	1
Permittee's Contact Information:	Select one:
	☐ New Survey
	☐ New Survey Series
	☐ Existing Survey Series
	☐ Time Extension
Permit #:	
Section 1: Pre-Survey Notification Package. Pleathe required documents are included in the Pre-Survey	
Pre-Survey Notification Form	
Navigation chart, as well as GPS coordinates (bounding coordinates for the survey area are known; all coordinates should be in decimal	acceptable if track lines are not
Résumé(s) of Marine Wildlife Monitor(s)	
Section 2: Pre-Survey Notices. Please use the bo have been sent to the following:	xes below to verify that notifications
U.S. Coast Guard Local Notice to Mariners	
Harbormasters' offices of regional harbors nea	ar the survey area
Section 3: Survey Details.	
Date(s) of operation (survey window):	
Number of survey days (approximate):	
Survey location:	
Hours of operation:	
Survey purpose/objective:	
The purpose of this survey is to map Zostera Pa	cifica beds in Santa Monica Bay.
1	

STATE OF CALIFORNIA - STATE LANDS COMMISSION GEOPHYSICAL SURVEY PERMIT - PRE-SURVEY NOTIFICATION FORM SLC 602

Section 4: Vessel Details.	
Vessel name:	
Vessel official number:	
Vessel captain's name:	
Radio channel(s) to be monitored by vessel:	

Section 5: Survey Equipment Characteristics.

Equipment type	
Frequency	540 kHz (Bathymetry and Side Scan) & 1600 kHz (Side Scan only)
Source level (dB re 1 uPa at 1 m [rms and peak])	
Number of beams	
Across and along track beamwidth	across = 100 deg along: 540 bathy = 0.5 deg; 540 kHz side scan = 0.36 deg along: 1600 kHz side scan = 0.2 deg
Pulse rate/length	rate: up to 60 Hz length: 540 side scan = 0.25 - 3.7 ms; 1600 = 0.12 - 1.12 ms
Rise time	
Source depth	
Tow speed	
Cable tow length	

STATE OF CALIFORNIA - STATE LANDS COMMISSION GEOPHYSICAL SURVEY PERMIT – PRE-SURVEY NOTIFICATION FORM SLC 602

Equipment type	
Frequency	
Source level (dB re 1 uPa at 1 m [rms and peak])	
Number of beams	
Across and along track beamwidth	
Pulse rate/length	
Rise time	
Source depth	
Tow speed	
Cable tow length	
Equipment type	
Frequency	
Source level (dB re 1 uPa at 1 m [rms and peak])	
Number of beams	
Across and along track beamwidth	
Pulse rate/length	
Rise time	
Source depth	
Tow speed	
Cable tow length	

Section 6: Safety Zones. For surveys operating equipment at a frequency < 200 kHz, a safety zone around the sound source is required. The size of the safety zone is based on the modeled or calculated distance to the 160 dB (rms) threshold, as outlined in Section 2100.07 (a)(5)(D) of the Geophysical Survey Permit Program's regulations. Please list the equipment-specific safety zones below.

Equipment type	Safety zone		
Section 7: Pinniped Haul-Out Sites, Marine F Permits/Authorizations. Please provide answe			
Are there pinniped haul-out sites within on near the survey area? If yes, please provide the ocation of and distance to the haul-out site(s).			
Are there MPAs within or near the survey area? distance to the MPA(s).	? If yes, please provide the location of and		

STATE OF CALIFORNIA - STATE LANDS COMMISSION GEOPHYSICAL SURVEY PERMIT - PRE-SURVEY NOTIFICATION FORM SLC 602

he California Department of Fish and Wildlife provide the type of permit and issuing agency	
Section 8: Contact Information. If you fores shing or other activities, please contact the	
Commission Representative	Bureau of Ocean Energy Management Representative (If Applicable)
	Representative (ii Applicable)
	Tropicoentative (ii Applicable)
	Tropicoentative (ii Applicable)

